

14" B&W 2 CHANNEL SWITCHER OBSERVATION SYSTEM WITH 2 NIGHT VISION CAMERAS

MODEL: SG14S1022P

FEATURES

- Sequentially view up to 2 camera locations
- 1 Way Audio
- Metal cabinet with 2 DIN & 2 RCA A/V Input and 1 RCA Slave A/V output
- ON/OFF standby button enables monitor screen to be turned off while recording
- Multi-voltage system 100 – 240 V AC
- Includes 2 B&W night vision cameras



Approvals: CE

 **LOREX**[®]



INTERNATIONAL

14" B&W 2 CHANNEL SWITCHER OBSERVATION SYSTEM

SPECIFICATIONS

MONITOR

Display Type:	14" B&W CRT
Video Format:	CCIR/EIA
Resolution:	300 TV Lines
Control:	Volume, Time, Brightness, Contrast
Camera Input:	DIN x 2, RCA x 2
A/V Input:	RCA 1 Set
A/V Output:	RCA 1 Set
A/V Slave Output:	RCA 1 Set
Operating Voltage:	100 ~ 240V AC, 50/60 Hz
Operating Temperature:	0 ~ 40 degrees C
Power Consumption:	35W
Dimensions (W x H x D):	322 x 317 x 317

CAMERA

Image Sensor:	1/4" B/W CMOS
Video format	CCIR
Effective pixels	352 H x 288 V
Resolution	280 TV lines
Sync system	Internal
AES	1/50 ~ 1/6000 sec
Min Illumination	1 LUX
Lens	3.6 MM F2
Viewing angle	Diagonal 70 degrees
Operating voltage	12 V DC
Operating Temperature:	-10 ~ 45°C
Weight:	340 Grams
Dimensions:	57mm W x 114mm D x 50mm H



INTERNATIONAL